

# PRECISION BALANCES APP/C



Precision balances series APP/C are offered in two solutions, weighing platform dimensions either 346×258 mm. Depending on the type, balances are equipped with backlit LCD display.

Each series of APP/C balances is offered with following capacities: 25, 30 and 6/35 kg. Independently on version, APP/C balance is based on electromagnetic measuring system, external calibration (internal for scales C/2) and RS 232 output.

Balance casing is made of aluminum, weighing pan is in stainless steel technology. Balances series APP have under hook weighing as standard solution.



Counting pieces



Density determination



Percentage

## Technical data:

	APP 25/C APP 25/C/2 *	APP 30/C APP 30/C/2	APP 6/35/C APP 6/35/C *
Max capacity	25 kg	30 kg	6/35 kg
Readability	0,1 g	0,1 g	1/5 g
Tare range	-25 kg	-30 kg	-35 kg
Repeatability	0,1 g	0,2 g	1/5 g
Linearity	±0,1 g	±0,3 g	±1/5 g
Pan size	346 × 258 mm		
Working temperature	+15° - +40 °C		
Operation time	3 s		
Power supply	230V / 11V AC or 120V / 11V AC		
Calibration weight	10 kg	10 kg	10 kg
Display	LCD (backlit)		

\* verified balances

## Additional equipment:

"KAFKA" THERMAL PRINTER	CALIBRATION WEIGHT
NEEDLE PRINTER "EPSON"	COMPUTER SOFTWARE: PW-WIN 2005
LCD ADDITIONAL DISPLAY	COMPUTER SOFTWARE: RAD-KEY 2000
EXTERNAL RECHARGEABLE BATTERY PACK	

**RADWAG**

26-600 Radom • Bracka Street 28 • POLAND • Phone: +48 48 3848800 • Fax: +48 48 3850010 • www.radwag.com • e-mail:export@radwag.com